

RO 30/50

kV dependent max mA values for exposure times $\leq 100\text{ms}$ in combination with Optimus 65/80kW

kV	SF [μA]	LF [μA]	kV	SF [μA]	LF [μA]	kV	SF [μA]	LF [μA]	kV	SF [μA]	LF [μA]
40	407000	628000	70	428571	714285	100	300000	500000	130	230769	384615
41	417600	639400	71	422535	704225	101	297029	495049	131	229007	381679
42	428200	650800	72	416666	694444	102	294117	490196	132	227272	378787
43	438800	662200	73	410958	684931	103	291262	485436	133	225563	375939
44	449400	673600	74	405405	675675	104	288461	480769	134	223880	373134
45	460000	685000	75	400000	666666	105	285714	476190	135	222222	370370
46	468400	694000	76	394736	657894	106	283018	471698	136	220588	367647
47	476800	703000	77	389610	649350	107	280373	467289	137	218978	364963
48	485200	712000	78	384615	641025	108	277777	462962	138	217391	362318
49	493600	721000	79	379746	632911	109	275229	458715	139	215827	359712
50	502000	730000	80	375000	625000	110	272727	454545	140	214285	357142
51	509800	737800	81	370370	617283	111	270270	450450	141	212765	354609
52	517600	745600	82	365853	609756	112	267857	446428	142	211267	352112
53	525400	753400	83	361445	602409	113	265486	442477	143	209790	349650
54	533200	761200	84	357142	595238	114	263157	438596	144	208333	347222
55	541000	769000	85	352941	588235	115	260869	434782	145	206896	344827
56	535714	777445	86	348837	581395	116	258620	431034	146	205479	342465
57	526315	785890	87	344827	574712	117	256410	427350	147	204081	340136
58	517241	794335	88	340909	568181	118	254237	423728	148	202702	337837
59	508474	802780	89	337078	561797	119	252100	420168	149	201342	335570
60	500000	811225	90	333333	555555	120	250000	416666	150	200000	333333
61	491803	819672	91	329670	549450	121	247933	413223			
	483870	806451	92	326086	543478	122	245901	409836			
	476190	793650	93	322580	537634	123	243902	406504			
	468750	781250	94	319148	531914	124	241935	403225			
	461538	769230	95	315789	526315	125	240000	400000			
	454545	757575	96	312500	520833	126	238095	396825			
	447761	746268	97	309278	515463	127	236220	393700			
	441176	735294	98	306122	510204	128	234375	390625			
	434782	724637	99	303030	505050	129	232558	387596			

These are the default values of the tube data file TUBE_R2.TDL or TUBE_R3.TDL.

Typically there are no changes after adaptation except there are reductions due to the max generator power (Optimus 50kW = 650mA max) or if the filament does not have its full emission anymore (e.g. from shorted filament loops).

The **red marked** emission current values (at 56kV SF and 61kV LF) are the max emission currents at a kV value from which on the filament current can be reduced to achieve its max load performance.